

MQ Power DCA-800SSK

From stationary standby power sources to mobile construction applications, MQ Power's WhisperWatt portable generators will meet your most demanding requirements.

WhisperWatt generators have been engineered to provide the highest reliability and maximum motor starting capability.



Performance Data		
Standby Output	704 kW , 880 kVA	
Prime Output	640 kW , 800 kVA	
Generator RPM	1800 RPMs	
Generator Design	Revolving Field Self-Ventilated Dip-Proof Single Bearing	
Voltage Regulation - (No Load to Full Load)	1 %	
Power Factor	0.8	
Armature Connection	Star with Neutral	
Excitation	Brushless with AVR	
No. Poles	4 Pole	
Frequency	60 Hz	
Available Voltages - 3 Phase	208, 220, 240, 416,440, 480 Reconnectable Volts	
Available Voltages - Single Phase	120, 127, 139, 240, 254, 277 Adjustable Volts	
Amps - Single Phase 120V	1777.8 (4 Wire) Amps	
Amps - Single Phase 240V	888.9 (4 Wire) Amps	
Amps - Three Phase 240V	1924 Amps	
Amps - Three Phase 480V	962 Amps	
Insulation	Class F	
Main Breaker Amps	2500	
Sound Level dB(A) - Full Load at 23 feet	73 dB(A)	
Power Source		
Engine Make / Model	Komatsu SA12V140	
Fuel Consumption	43.7 gal/hr full load	33.0 gal/hr ¾ load
	24.0 gal/hr ½ load	14.9 gal/hr ¼ load
Fuel Tank Capacity	129 Gal Internal	1150 Gal Trailer
Dimensions (Without Trailer)		
Overall Length	241 in. , 611 cm	
Overall Width	77 in. , 195 cm	
Overall Height	98 in. , 250 cm	
Approx. Net Wt. Dry	24692 lbs. , 11200 kg.	